

KENWOOD

Listen to the Future

NEXEDGE®

NXR-710/810

NEXEDGE® VHF/UHF Digital & FM Base Units

NXDN®

● GENERAL FEATURES

- 136 - 174 MHz, 5 - 50 W
- 400 - 470 MHz, 5 - 40 W
- Repeater Operation
- Duplex / Simplex Base Operation
- 30 CH Scanning Base
- Two-Digit LED Display
- 6 Lighted Programmable Function Keys
- Front Panel Speaker
- Rear External Speaker Output (4 Watts Audio)
- Volume Control
- Microphone Jack
- Programmable AUX I/O's
- DTMF Front Panel PF Key Control
- DTMF AUX Output Control
- DTMF AUX Input Monitoring
- External Frequency Reference (10 MHz) Connectivity
- Windows® PC Programming
- Flash Firmware Upgrading

● DIGITAL – CONVENTIONAL MODE

- NXDN® Digital Air Interface
- Conventional IP Network*
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Mixed FM / Digital Operation
- NXDN® Scrambler Built-in
- 16 RAN Repeater Control Built-in
- 1,000 GIDs Per Site
- 1,000 UIDs Per Site
- NXR Over-the-Air Alias

● FM MODES – GENERAL

- VHF: 25, 20 & 12.5 kHz Channels
- UHF: 25, 20 & 12.5 kHz Channels
- Built-in Scrambler

● FM CONVENTIONAL MODE

- 16 QT / DQT Repeater Control Built-in
- Hang Timer / Time Out Timer / CW ID
- External FM Controller Interface
- EIA Voter Tone Generation

● FM TRUNKED MODE

- External MPT Controller Interface

* Future availability



<http://nexedge.kenwood.com>

Options

■ **KMC-30**
Microphone



■ **KMC-9C**
Desktop Microphone



■ **KMC-35**
Microphone



■ **KES-5**
External Speaker



All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

	NXR-710	NXR-810
GENERAL		
Frequency Range	136 - 174 MHz	400 - 470 MHz
Number of Channels	30	
Channel Spacing	Analogue 12.5 / 20 / 25 kHz Digital 6.25 / 12.5 kHz	
PLL Channel Step	2.5 / 3.125 kHz	3.125 / 5 kHz
Current Drain	Standby 0.5 A Receive 1.0 A Transmit 11.0 A	
Duty Cycle (TX, RX)	100% at 25W, 50% at maximum power	
Frequency Stability	± 1.0 ppm	
Operating Voltage	13.2 V DC (10.8 - 15.6 V DC)	
Operating Temperature Range	-30°C to +60°C	
Antenna Impedance	50 Ω	
Dimensions (W x H x D), Projections not included	483 x 88 x 340 mm	
Weight (net)	9.7 kg	
Applicable Standards	ETSI R&TTE EN 300 086, EN 300 113, EN 300 219, ETSI Safety EN301 489, EN 301 166 EN 60065, EN 60950-1, EN 60215	
RECEIVER		
Sensitivity (Analogue)	0.28 μV	
(25kHz / 20kHz / 12.5kHz)	-3 dBμV (0.35 μV)	
Sensitivity (Digital)	0.28 μV / 0.22 μV	
(12.5kHz / 6.25kHz)	-4 dBμV (0.32 μV) / -6 dBμV (0.25 μV)	
Adjacent Channel Selectivity (Analogue)	83 dB / 81 dB / 77 dB	
(25kHz / 20kHz / 12.5kHz)	80 dB / 78 dB / 74 dB	
Intermodulation (Analogue)	72 dB	
Spurious Response Rejection (Analogue)	85 dB	
Audio Distortion	Less than 2.5% at 1000 Hz	
Audio Output	4 W (at 4 Ω, less than 5% distortion)	
TRANSMITTER		
RF Power Output	5 W to 50 W	5 W to 40 W
Modulation Limiting (Analogue)	±5.0 kHz at 25 kHz ±4.0 kHz at 20 kHz ±2.5 kHz at 12.5 kHz	
Spurious Emission	-36 dBm ≤ 1 GHz, -30 dBm > 1 GHz	
FM Noise (EIA)	55 dB / 53 dB / 50 dB	
(Analogue, 25kHz / 20kHz / 12.5kHz)	Less than 1% at 1000 Hz	
Modulation Distortion	16K0F3E, 14K0F3E, 14K0F2D, 12K0F2D, 8K50F3E, 7K50F2D, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analogue measurements made per EN 300 086 and 113.
Digital measurements made per EN 300 113 and EN301 166.
Specifications shown are typical.

Kenwood follows a policy of continuous advancement in development.
For this reason specifications may be changed without notice.

AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows® is a registered trademarks of Microsoft Corporation.
NXDN® is a registered trademark of Kenwood Corporation and Icom Inc.
NEXEDGE® is a registered trademark of Kenwood Corporation.

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

KENWOOD CORPORATION

2967-3, Ishikawa-Cho, Hachioji-Shi, Tokyo 192-8525, Japan

global communications

Reg. No. 1987/003508/07
Highway Business Park, Park Street, Rooihuiskraal, Centurion
P.O. Box 27, The Reeds 0061, PRETORIA, RSA
Tel: +27 12 621 0400 Fax: +27 12 661 0388
e-mail: kenwood@globalcomms.co.za
Home page: www.globalcomms.co.za



KENWOOD

Listen to the Future

YOUR LOCAL DEALER

